



**Key Specifications**

<b>89</b>	<b>55"</b>	<b>14.5"</b>
HORSEPOWER	VEHICLE WIDTH	GROUND CLEARANCE

**Engine & Drivetrain**

Active Descent Control	Standard
Cooling	Liquid
Cylinders Displacement	2 / 952cc
Drive System Type	One Touch On-Demand AWD/2WD
Engine Braking System (EBS)	Standard
Engine Type	ProStar SOHC 4-Stroke Twin Cylinder
Fuel System/Battery	Electronic Fuel Injections / 400 CCA
Horsepower	89 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H In-line Shifting

**Dimensions**

Bed Box Dimensions (L x W x H)	N/A
Dry Weight	970 lb (440 kg)
Front/Rear Rack	200 lb / 300 lb (91 kg / 136 kg)
Fuel Capacity	5.25 gal (19.9 L)
Ground Clearance	14.5 in (36.8 cm)
Overall Vehicle Size (L x W x H)	82.5 x 55 x 49.5 in (209.5 x 140 x 125.7 cm)
Payload Capacity	715 lbs (324 kg) (includes operator, cargo and accessories)
Person Capacity	1
Seat Height	37 in (94 cm)
Wheelbase	56.8 in (144.27 cm)

**Brakes**

Front/Rear Brakes	Single Lever 4-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake
Parking Brake	Park In-Transmission / Lockable Hand Lever

**Additional Specifications**

Cargo System	Lock & Ride 4 Gal (15L) Front, 2 Gal (8L) Rear
Front Suspension	Sealed Dual A-Arm 11.6 in (29.5 cm) Travel
Hitch Towing Rating	1,750 lb (794 kg)
Hitch Type	Standard 2 in (5 cm) Receiver
Instrumentation	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet
Lighting	Halogen Triple 50W High Beams Dual 50w Low Beam Headlight Triple LED Brakelights/Taillights
Other Standard Features	Front Bumper, Rear Bumper, 3,500 lb. Winch, Cut and Sew Seat, Painted Plastics, In Pod Battery Charge Port
Rear Suspension	Sealed Dual A-Arms Rolled IRS, 14 in (35.6 cm) Travel

**Tires / Wheels**

Electronic Power Steering	Standard
Front Tires	27 x 9 Duro PowerGrip V2
Rear Tires	27 x 11 Duro PowerGrip V2
Wheels	14 in Aluminum