

#### **Key Specifications**

90

47.6"

12"

HORSEPOWER

VEHICLE WIDTH

GROUND CLEARANCE

### **Engine & Drivetrain**

| <u> </u>                    |  |
|-----------------------------|--|
| Active Descent Control      | Standard                                 |
| Cooling                     | Liquid                                   |
| Cylinders Displacement      | 2 / 952cc                                |
| Drive System Type           | One Touch On-Demand AWD/2WD              |
| Engine Braking System (EBS) | Standard                                 |
| Engine Type                 | ProStar SOHC 4-Stroke Twin Cylinder      |
| Fuel System/Battery         | Electronic Fuel Injections / 400 CCA     |
| Horsepower                  | 90 HP                                    |
| Transmission/Final Drive    | Automatic PVT P/R/N/L/H In-line Shifting |

#### **Dimensions**

| N/A  |
|--|
| 801 lb (363 kg)                                    |
| 120 lb /240 lb (55 kg / 110 kg)                    |
| 5.25 gal (19.9 L)                                  |
| 12 in (30.5 cm)                                    |
| 83.25 x 47.6 x 50.75 in (211.4 x 120.9 x 128.9 cm) |
| 575 lb (261 kg)                                    |
| 37 in (94 cm)                                      |
| 53 in (134.6 cm)                                   |
|  |

### Brakes

| Front/Rear Brakes | Single Lever 4-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake |
|-------------------|--|
| Parking Brake     | Park In-Transmission / Lockable Hand Lever                         |

# **Additional Specifications**

| Cargo System            | Lock & Ride, 2 Cast Rack Extenders 4 Gal (15 L) Front Dry Storage 2 Gal (8 L) Rear Storage  |
|-------------------------|---|
| Front Suspension        | Straight Dual A-Arm 9 in (22.9 cm) Travel   |
| Hitch Towing Rating     | 1,500 lb (680.4 kg)   |
| Hitch Type              | Standard 1.25 in (3.2 cm) Receiver  |
| Instrumentation         | All Digital Gauge, Speedometer, Odometer, Tachometer, Two<br>Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator,<br>Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet |
| Lighting                | 50w High Beam, Dual 50w Low Beam Headlights   |
| Other Standard Features | 6 Rack Extenders, In Pod Battery Charge Port, Painted Plastics  |
| Rear Suspension         | Straight Dual A-Arm, Rolled IRS, 10.25 in (26 cm) Travel  |
|                         |   |

## Tires / Wheels

| Electronic Power Steering | Standard        |
|---------------------------|-----------------|
| Front Tires               | 26 x 8-14; CST  |
| Rear Tires                | 26 x 10-14; CST |
| Wheels                    | 14 in Aluminum  |