

## RANGER XP 1000 High Lifter Ghost Gray

**RANGER**


### Key Specifications

<b>82</b>	<b>3</b>	<b>15"</b>
<b>Horsepower</b>	<b>Person Capacity</b>	<b>Ground Clearance</b>

### Engine & Drivetrain

Cooling	Liquid
Cylinders Displacement	999cc
Drive System Type	High Performance On-Demand AWD/2WD
Engine Type	4-Stroke Twin Cylinder DOHC
Fuel System/Battery	Electronic Fuel Injection
Horsepower	82 HP
Transmission/Final Drive	Automatic PVT H/L/N/R/P; Shaft

### Dimensions

Bed Box Dimensions (L x W x H)	36.75 x 54.25 x 12.5 in (93.3 x 137.8 x 31.75 cm)
Box Capacity	1,000 lb (454 kg)
Estimated Dry Weight	1,775 lb (805 kg)
Fuel Capacity	11.5 gal (43.5 L)
Ground Clearance	15 in (38.1 cm)
Hitch Towing Rating	2,500 lb (1,133.9 kg)
Overall Vehicle Size (L x W x H)	122 x 65 x 78 in (310 x 165 x 198 cm)
Payload Capacity	1,880 lb (989 kg)
Person Capacity	3
Wheelbase	81 in (206 cm)

### Brakes

Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
Parking Brake	Park In-Transmission

### Additional Specifications

Adjustable Driver Seat	Standard
Cargo System	Lock & Ride
Hitch Type	Standard 2 in (5 cm) Receiver
Instrumentation	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet
Lighting	Halogen Headlamps, 55W Low Beam, 60W High Beam, Dual LED Taillamps
Other Standard Features	Premium Half Doors, Mud Specific Front and Rear Bumpers, Polaris PRO HD 4,500 Lb. Winch, Arched A-Arms, Premium Cut & Sew Seats, Premium Steering Wheel and Interior Accents, Rearview Mirror, Polaris Pulse Electrical System (6 position), Standard In-Dash SAE Charge Port
Tilt Steering	Standard

### Tires / Wheels

Electronic Power Steering	Standard
Front Tires	30 x 9.5-14; Outlaw 2
Rear Tires	30 x 11-14; Outlaw 2
Wheels	14 in Black Aluminum

### Suspension

Front Suspension	Independent, Arched Lower A-arms, 10" (25.4 cm) of Travel
Rear Suspension	Independent, Arched Lower A-arms, 10" (25.4 cm) of Travel